

LAKFA

LOCKING[®] THREADLOCKER



maksimum
+200°



Fast
Curing 

Initial Cure ●
10 ~ 20Min.

Completely Cure ●
6 ~ 24 Hour

minimum
-50° 



AKFA LOCKING®

Adhesives and Pipe Sealants



LOCKING[®] 343

THREADLOCKER REMOVABLE, SEALING ELEMENT

Locking 343 pipe seal,

It is removable, blue in color, medium viscosity.

Thanks to the active ingredients, it does not drip,

With its medium strength and detachable formula

Provides easy use.


It is resistant to low and high temperatures.

Resistant to many solvents, gases,

water and pressures

It shows excellent resistance.

PACKAGING INFORMATION



250ml



50ml



15ml



Product Code	343
Interior View	Liquid
Colour	Blue
Contents	Methacrylate Ester
Strength	Middle
Temperature Range (C°)	-50° <> +150°
Viscosity (cP @ 2.5rpm)	7000 - 15000 mPas
Intensity (g / ml)	1030
Shelf Life	24 Month

AKFA

LOCKING®

Adhesives and Pipe Sealants



LOCKING[®] 338

THREADLOCKER

HIGH STRENGTH, RETAINING

Locking 338 High strength, retaining,

It is green in color and has medium viscosity.

Thanks to the active ingredients, it does not drip,

It shows high heat and high strength,

It offers easy use.

It is resistant to low and high temperatures.

Resistant to many solvents,

gases, water and pressures

It shows excellent resistance.



Adhesives and Pipe Sealants

Product Code 338

Interior View Liquid

Colour Green

Contents Methacrylate Ester

Strength High

Temperature Range (C°) -50° <> +200°

Viscosity (cP @ 2.5rpm) 4000 - 4500 mPas

Intensity (g / ml) 1040

Shelf Life 24 Month

PACKAGING INFORMATION



250ml



50ml



15ml



LOCKING®

Adhesives and Pipe Sealants



LOCKING[®] 342

THREADLOCKER HIGH STRENGTH, HIGH TEMPERATURE

Locking 342,

It is red in color and has medium viscosity.

Thanks to the active ingredients, it does not drip,

It shows high strength. low and

It is resistant to high temperatures.

Provides easy use.

Resistant to many solvents,

gases, water and pressures

It shows excellent resistance.

PACKAGING INFORMATION



250ml



50ml



15ml



Adhesives and Pipe Sealants

Product Code 342

Interior View Liquid

Colour Red

Contents Methacrylate Ester

Strength High

Temperature Range (C°) -50° <> +200°

Viscosity (cP @ 2.5rpm) 3000 - 5000 mPas

Intensity (g / ml) 1030

Shelf Life 24 Month



AKFA LOCKING®

Adhesives and Pipe Sealants



LOCKING[®] 370

THREADLOCKER

HIGH STRENGTH, NUTLOCK

Locking 370,

It is a high-strength stabilizer,

It is green in color and has medium viscosity.

Thanks to the active ingredients, it does not drip,

high strength and high heat resistant

It provides easy use with its formula.

It is resistant to low and high temperatures.

Resistant to many solvents, gases,

water and pressures It shows excellent resistance.

PACKAGING INFORMATION



250ml



50ml



15ml



Adhesives and Pipe Sealants

Product Code	370
Interior View	Liquid
Colour	Green
Contents	Methacrylate Ester
Strength	High
Temperature Range (C°)	-50° <> +200°
Viscosity (cP @ 2.5rpm)	3000 - 4000 mPas
Intensity (g / ml)	1040
Shelf Life	24 Month

AKFA LOCKING®

Adhesives and Pipe Sealants



LOCKING[®] 377

THREADLOCKER

LARGE DIAMETER, REMOVABLE

Locking 377 large diameter thread, pipe seal,

It is yellow in color and has medium viscosity.

Paste thanks to the active ingredients in the form non-drip, medium strength and

It provides easy use with its removable formula.

It is resistant to low and high temperatures.

Resistant to many solvents,

gases, water and pressures

It shows excellent resistance.

PACKAGING INFORMATION



250ml



50ml



Product Code Locking 377

Interior View Paste

Colour Sari

Contents Methacrylate Ester

Strength Middle

Temperature Range (C°) -50° <> +150°

Viscosity (cP @ 2.5rpm) 40000 - 60000 mPas

Intensity (g / ml) 1020

Shelf Life 24 Month



AKFA

LOCKING®

Adhesives and Pipe Sealants




LOCKING[®] L-42

THREADLOCKER REMOVABLE, MEDIUM STRENGTH

Locking L-42 medium strength pipe sealing,
It is removable, blue in color, medium viscosity.
Thanks to the active ingredients, it does not drip,
With its medium strength and detachable
formula provides easy use.
It is resistant to low and high temperatures.
Resistant to many solvents, gases,
water and pressures It shows excellent resistance.

PACKAGING INFORMATION



250ml



50ml



15ml



Product Code Locking L-42

Interior View Liquid

Colour Blue

Contents Methacrylate Ester

Strength Middle

Temperature Range (C°) -50° <> +150°

Viscosity (cP @ 2.5rpm) 4000 - 5000 mPas

Intensity (g / ml) 1030

Shelf Life 24 Month





OUR CERTIFICATES



CERTIFICATE

**AKFA ENDÜSTRİ
SANAYİ VE TİCARET ANONİM ŞİRKETİ**
CİHANGİR MAH. GÜVERCİN CAD. NO:2 İÇ KAPI NO:22
AVCILAR / İSTANBUL / TÜRKİYE

*Has been assessed and found to comply with the requirements of:
Denetlenmiş ve aşağıdaki standardın gerekliliklerine uygunluğu görülmüştür:*

ISO 14001:2015

*The Environmental Management System is applicable to
Çevre Yönetim Sistemi:*

PRODUCTION AND SALES OF GLUE (CASEIN-BASED, ANIMAL-BASED, STARCH-BASED, RUBBER-BASED, PLASTIC-BASED, POLYMER-BASED) AND ANAEROBIC PIPE SEALANT

TUTKAL (KAZEİN ESASLI, HAYVANSAL ESASLI, NIŞASTA ESASLI, KAUCUK ESASLI, PLASTİK ESASLI, POLİMER ESASLI) VE ANAEROBİK BORU SIZDIRMAZLIK ELEMANI ÜRETİMİ VE SATIŞI

Certificate Number: EMS-0114348 Belge Numarası: EMS-0114348	Initial Certification Date: 04.12.2023 İlk Belgelendirme Tarihi: 04.12.2023
Certification Period: 3 Years Belgelendirme Periyodu: 3 Yıl	Certificate Validity Date: 03.12.2024 Belge Geçerlilik Tarihi: 03.12.2024



ACCREDITED
Management Systems
Certification Body
MSCB-135



IQR Sertifikasyon Onayı



IQR ULUSLARARASI BELGELENDİRME HİZMETLERİ LTD.ŞTİ.
Beşevler Mah. Kocayunus Sk. No:3 Arslan Han Plaza K2 Nilüfer / BURSA
Tel.: +90.224.266 00 16 Faks: +90.224.249 41 13 www.iqrcert.com e-posta: info@iqrcert.com



CERTIFICATE

**AKFA ENDÜSTRİ
SANAYİ VE TİCARET ANONİM ŞİRKETİ**
CİHANGİR MAH. GÜVERCİN CAD. NO:2 İÇ KAPI NO:22
AVCILAR / İSTANBUL / TÜRKİYE

In recognition of the organization's Managements System which complies with

ISO 45001:2018

The scope of activities covered by this certificate is defined below

PRODUCTION AND SALES OF GLUE (CASEIN-BASED, ANIMAL-BASED, STARCH-BASED, RUBBER-BASED, PLASTIC-BASED, POLYMER-BASED) AND ANAEROBIC PIPE SEALANT

TUTKAL (KAZEİN ESASLI, HAYVANSAL ESASLI, NIŞASTA ESASLI, KAUCUK ESASLI, PLASTİK ESASLI, POLİMER ESASLI) VE ANAEROBİK BORU SIZDIRMAZLIK ELEMANI ÜRETİMİ VE SATIŞI

Certificate Number : GCR/CERT-12.2023.4089
Certificate Issue Date : 04.12.2023
Certificate Validity : 03.12.2024

Abimanyu Gaurav

Abimanyu Gaurav
Approval





For updated information concerning the present certificate visit at www.gccert.co.in
Global Certification & Register Services Limited
NO.2-3-189/73/4, 2nd floor, akshaya , shobana colony, BALANAGAR INDIA
certification@gccert.co.in
www.gccert.co.in

AKFA

LOCKING®

OUR CERTIFICATES




GCR CERT

CERTIFICATE

Attestation of Conformity
Uygunluk Beyanı

Manufacture Name:
Örnek Adı:
AKFA ENDÜSTRİ SANAYİ VE TİCARET ANONİM ŞİRKETİ

Manufacturer Address:
Örnek Adres:
CİHANGİR MAH. GÜVERCİN CAD. NO:2 İÇ KAPI NO:22 AVCILAR / İSTANBUL / TÜRKİYE

The product groups defined below have been fulfilled and the responsibility of the applicable requirements of General Product Safety Directive 2001/95/EC has been accepted by AKFA ENDÜSTRİ SANAYİ VE TİCARET ANONİM ŞİRKETİ

The product groups defined below are subject to internal production controls, depending on AKFA ENDÜSTRİ SANAYİ VE TİCARET ANONİM ŞİRKETİ

It has been checked by:

In this context, it belongs to the company where the responsibility is fulfilled.

Aşağıda tanımlanmış olan ürün grupları Genel Ürün Güvenliği Direktifi 2001/95/AT'nin uygulanabilen gerekliliklerinin yerine getirildiği ve sorumluluğunun alınmış olduğu AKFA ENDÜSTRİ SANAYİ VE TİCARET ANONİM ŞİRKETİ tarafından kabul edilmiştir. Aşağıda tanımlanmış ürün grupları, iç tetçim kontrollerine bağlı olarak, AKFA ENDÜSTRİ SANAYİ VE TİCARET ANONİM ŞİRKETİ tarafından kontrol edilmiştir. Bu kapsamda sorumluluğun yerine getirildiği firmaya aittir.

Description of Product:
Ürün Açıklaması:
ANAEROBİK PIPE SEAL
ANAEROBİK BORU SIZDIRMAZLIK ELEMANI

Product Model:
Ürün Modelleri:
LOCKING 343
LOCKING 377
LOCKING 342
LOCKING 370
LOCKING L-42
LOCKING 338

Related Directives:
İlgili Direktifler:
GENERAL PRODUCT SAFETY DIRECTIVE 2001/95/EC
GENEL ÜRÜN GÜVENLİĞİ DİREKTİFİ 2001/95/AT

Certificate Number : GCR/CERT-11.2023.4060
Certificate Issue Date : 30.11.2023
Certificate Validity : 29.11.2024


Abimanyu Gaurav
Approval


For updated information concerning the present certificate visit at www.gcrCERT.co.in
Global Certification & Register Services Limited
NO.3-5-180/73/4, 3rd floor, Ashraya, shobana colony, BALANAGAR INDIA
certification@gcrCERT.co.in
www.gcrCERT.co.in



CERTIFICATE

**AKFA ENDÜSTRİ
SANAYİ VE TİCARET ANONİM ŞİRKETİ**

CİHANGİR MAH. GÜVERCİN CAD. NO:2 İÇ KAPI NO:22
AVCILAR / İSTANBUL / TÜRKİYE

*Has been assessed and found to comply with the requirements of:
Denetlenmiş ve aşağıdaki standartın gerekliliklerine uygunluğu görülmüştür:*

ISO 9001:2015

*The Quality Management System is applicable to:
Kalite Yönetim Sistemi:*

PRODUCTION AND SALES OF GLUE (CASEIN-BASED, ANIMAL-BASED, STARCH-BASED, RUBBER-BASED, PLASTIC-BASED, POLYMER-BASED) AND ANAEROBIC PIPE SEALANT

TUTKAL (KAZEİN ESASLI, HAYVANSAL ESASLI, NIŞASTA ESASLI, KAUCUK ESASLI, PLASTİK ESASLI, POLİMER ESASLI) VE ANAEROBİK BORU SIZDIRMAZLIK ELEMANI ÜRETİMİ VE SATIŞI

Certificate Number: QMS-0114348 Belge Numarası: QMS-0114348	Initial Certification Date: 04.12.2023 İlk Belgelendirme Tarihi: 04.12.2023
Certification Period: 3 Years Belgelendirme Periyodu: 3 Yıl	Certificate Validity Date: 03.12.2024 Belge Geçerlilik Tarihi: 03.12.2024


IAS
ACCREDITED
Management Systems
Certification Body
MSCB-135


IQR
IQR Sertifikasyon Onayı



IQR ULUSLARARASI BELGELENDİRME HİZMETLERİ LTD.ŞTİ.
Beşevler Mah. Kocayunus Sk. No:3 Arslan Han Plaza K2 Nilüfer / BURSA
Tel.: +90.224.268 00 16 Faks: +90.224.249 41 13 www.iqrcert.com e-posta: info@iqrcert.com



LOCKING®
THREADLOCKER

+90 533 643 41 55 • info@akfaendustri.com

Cihangir Neighbourhood Güvercin Street No: 2/22 Aktim 3 İş Merkezi Avcılar/İstanbul • TÜRKİYE

www.akfaendustri.com